



ELEVATOR LIGHTS

DESCRIPTION

3W LED replacement lamp for elevators and other small applications.

FEATURES

- Instant-on with no warmup
- Lasts 20x longer than incandescent for reduced replacement and maintenance costs
- Uses up to 90% less energy than incandescent or halogen
- Shatter-resistant for reduced risk of injury and breakage

WARRANTY

- 3 year limited warranty; see eiko.com for warranty details

APPLICATIONS

- Elevators
- Property Management
- Hospitality
- Retail
- Aircraft
- Hospitals
- Office Lighting
- Shopping Malls
- Parking Garages



RoHS  Compliant

| | | |
|---------------------|-------------------|------------------------------------|
| PERFORMANCE | Power Consumption | 3W |
| | Lumens | 125 |
| | Efficacy (LPW) | 42 |
| | CRI | 70+ |
| | CCT | 3000K, 4000K |
| | Life (L70) | 20,000/30,000 hours |
| ELECTRICAL | Power Factor | ≥0.9 |
| | THD | <20% |
| CONSTRUCTION | Base | BA15d, BA15s |
| LISTINGS | Material Usage | RoHS Compliant; no mercury or lead |

PERFORMANCE SUMMARY

GBF NON-DIMMABLE BA15D BASE - 12V AC/DC:

| Order Code | Item # | Lumens | Watts | CCT | CRI | Beam | MOL | Life/Hours | Replaces Halogen |
|------------|--------------------|--------|-------|-------|-----|------|-------|------------|------------------|
| 08895 | LED3WGBF/30/830-G5 | 125 | 3W | 3000K | 80+ | 30° | 1.77" | 20,000 | 20W GBF |
| 08900 | LED3WGBF/30/840-G5 | 125 | 3W | 4000K | 75+ | 30° | 1.77" | 20,000 | 20W GBF |

1383 NON-DIMMABLE BA15S BASE - 12V AC/DC:

| Order Code | Item # | Lumens | Watts | CCT | CRI | Beam | MOL | Life/Hours | Replaces Halogen |
|------------|---------------------|--------|-------|-------|-----|------|-------|------------|------------------|
| 08896 | LED3W1383/30/830-G5 | 125 | 3W | 3000K | 80+ | 30° | 2.48" | 20,000 | 20W 1383 |
| 08899 | LED3W1383/30/840-G5 | 125 | 3W | 4000K | 75+ | 30° | 2.48" | 20,000 | 20W 1383 |

NOTE: Use order code when ordering.

DIMENSIONS

